

1 EU-TYPE EXAMINATION CERTIFICATE



2 **Equipment or Protective systems intended for use in Potentially
Explosive Atmospheres - Directive 2014/34/EU**

3 **EU-Type Examination Certificate No: FM18ATEX0057X**

4 **Equipment or protective system: D Series Network Ethernet Cameras
(Type Reference and Name)**

5 **Name of Applicant: Spectrum Camera Solutions LLC**

6 **Address of Applicant: 8935 Alameda Genoa Road
Houston, TX 77075
United States of America**

7 This equipment or protective system and any acceptable variation thereto is specified in the schedule to this certificate and documents therein referred to.

8 FM Approvals Europe Ltd, notified body number 2809 in accordance with Article 17 of Directive 2014/34/EU of 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential report number:

3064118 dated 9th August 2018

9 Compliance with the Essential Health and Safety Requirements, with the exception of those identified in item 15 of the schedule to this certificate, has been assessed by compliance with the following documents:

EN IEC 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014
and EN 60529:1991+A1:2000+A2:2013

10 If the sign 'X' is placed after the certificate number, it indicates that the equipment is subject to specific conditions of use specified in the schedule to this certificate.

11 This EU-Type Examination certificate relates only to the design, examination and tests of the specified equipment or protective system in accordance to the directive 2014/34/EU. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.

12 The marking of the equipment or protective system shall include:



II 2 G Ex db IIB+H2 T6 Gb Ta = -20°C to +55°C

II 2 D Ex tb IIIC T85°C Db Ta = -20°C to +55°C

Martin Crowe
Certification Manager, FM Approvals Europe Ltd.

Issue date: 14th June 2022

THIS CERTIFICATE MAY ONLY BE REPRODUCED IN ITS ENTIRETY AND WITHOUT CHANGE

FM Approvals Europe Limited, One Georges Quay Plaza, Dublin. Ireland. D02 E440
T: +353 (0) 1761 4200 E-mail: atex@fmaprovals.com www.fmaprovals.com

F ATEX 020 (Dec/2020)



SCHEDULE



Member of the FM Global Group

to EU-Type Examination Certificate No.FM18ATEX0057X

13 Description of Equipment or Protective System:

General/Construction - The D Series Network Ethernet Cameras are designed to provide visual monitoring in hazardous environments. The D Series Network Ethernet Cameras consist of a dual-compartment, cylindrical housing with a thread-on blind wiring compartment cover and a thread-on dome window camera compartment cover. The housings are available in either 316 stainless steel or 6061-T6 aluminium alloy. The window cover consists of a dome lens cemented in place. There are three M20 openings between the wiring compartment and the camera compartment. The openings are closed by two M20 plugs and one cemented Ethernet cable bushing. The wiring compartment contains two M20 entries. The D Series Cameras utilize the same wiring compartment and dome window cover. The main difference is the size of the camera compartment with the D100, D200, D300, D400 and D500 having an approximate housing length of 3.32 inches (84mm), 7.75 inches (197mm), 4.5 inches (114mm), 5 inches (127mm) and 5.5 inches (140 mm), respectively. The D Series cameras can also be ordered in custom housing lengths from 84 mm to 196 mm (eg. D084 to D196). The optional breather/drain is ATEX certified as Flameproof, II2G Ex db IIC Gb; and Protection by enclosure, II 1D Ex ta IIIC Da under CML certificate 18ATEX1330U.

Ratings - The D Series Network Ethernet Cameras can be supplied with a variety of cameras (in accordance with EN60950 or EN62368) complying with the IEEE802.3af, 802.3at, 802.3at++ or 802.3bt PoE (Power over Ethernet) standard (57Vdc max). Voltage and wattage shall not exceed the maximum tested configuration of 57Vdc (60W). The D Series Network Ethernet Cameras are rated for use in an ambient temperature range of -20°C to +55°C and are IP66/67 (IP67 is not applicable when supplied with optional breather/drain). The camera within the enclosure may be placed in any arrangement provided that an area of at least 40% of each cross-sectional area remains free to permit unimpeded gas flow and, therefore, unrestricted development of an explosion. Separate relief areas may be aggregated provided each area has a minimum dimension in any direction of 12.5mm.

Dab-c-d-e.Network EthernetCamera.

- a= Housing length 1, 2, 3, 4 or 5 (or any three digits from 084 to 196 representing custom housing lengths in mm).
- b= Camera manufacturer code (two digits) 01 to 99.
- c= Material A or S.
- d= Several characters representing the camera manufacturer's part number (may contain additional dashes).
- e= Optional breather/drain BLANK or BD. (IP67 is not applicable when supplied with optional breather/drain).

14 Specific Conditions of Use:

1. The flameproof joints of the equipment are not intended to be repaired. Consult the manufacturer if dimensional information on the flameproof joints is necessary.
2. Follow the manufacturer's instructions to reduce the potential of an electrostatic charging hazard on the surface of the equipment in Group II and III environments.
3. The equipment meets the requirements according to the low level risk of mechanical danger. Therefore, the equipment shall be located and installed such that the risk of impact or other mechanical damage is reduced or avoided.

15 Essential Health and Safety Requirements:

The relevant EHSRs that have not been addressed by the standards listed in this certificate have been identified and assessed in the confidential report identified in item 8.

THIS CERTIFICATE MAY ONLY BE REPRODUCED IN ITS ENTIRETY AND WITHOUT CHANGE

FM Approvals Europe Limited, One Georges Quay Plaza, Dublin, Ireland. D02 E440
T: +353 (0) 1761 4200 E-mail: atex@fmaprovals.com www.fmaprovals.com

F ATEX 020 (Dec/2020)

SCHEDULE

to EU-Type Examination Certificate No.FM18ATEX0057X

16 Test and Assessment Procedure and Conditions:

This EU-Type Examination Certificate is the result of testing of a sample of the product submitted, in accordance with the provisions of the relevant specific standard(s), and assessment of supporting documentation. It does not imply an assessment of the whole production.

Whilst this certificate may be used in support of a manufacturer's claim for CE Marking, FM Approvals Europe Ltd accepts no responsibility for the compliance of the equipment against all applicable Directives in all applications.

This Certificate has been issued in accordance with FM Approvals Europe Ltd's ATEX Certification Scheme.

17 Schedule Drawings

A list of the significant parts of the technical documentation is annexed to this certificate and a copy has been kept by the Notified Body.

18 Certificate History

Details of the supplements to this certificate are described below:

Date	Description
29th August 2018	Original Issue.
15th July 2019	Supplement 1: Report Reference: RR219244 dated 8th July 2019. Description of the Change: Minor documentation changes not affecting the product safety. Certificate transferred from FM Approvals Ltd., notified body no. 1725, to FM Approvals Europe Ltd., notified body no. 2809.
27th January 2021	Supplement 2: Report Reference: RR226618 dated 26th January 2021. Description of the Change: Revise the product description to correct minor errors and to remove references to intellectual property.
14th June 2022	Supplement 3: Report Reference: PR462443 dated 9th June 2022. Description of the Change: New dome lens backing ring was evaluated as part of this project. EN 60079-0 examination updated to the 2018 edition. Other minor documentation changes not affecting the equipment safety.

THIS CERTIFICATE MAY ONLY BE REPRODUCED IN ITS ENTIRETY AND WITHOUT CHANGE